Standards & Specifications

United TRAILERS SPECIFICATIONS

	U Tag	UFW/UGN	UW Tag	UV Tag	USN Tag
Independent Torsion Suspension Axles	•	•	•	•	•
E-Z Lube HubsÈ	•	•	•	•	•
Radial Tires	•	•	•	•	•
White Spoke Wheels	•	•	•	•	•
Aerodynamic Front Cap	•	•	•	•	•
Light-Weight Steel Uni-Body Construction	•	•	•	•	•
Aluminum Fenders or Flares	•	•	•	•	•
3/8ò Plywood Interior Wall Liner	•	•	•	•	•
Weather Guard Coating on Fasteners	•	•	•	•	•
L.E.D. Tail Lights and Clearance Lights	•	•	•	•	•
One Piece Aluminum Roof	•	•	•	•	•
24ò Aluminum Stone Guard on Tag Models	•	na	•	•	•
48ò Aluminum Stone Guard on FW/GN Models	na	•	na	na	na
Double Rear Doors with Camlock	•	•	•	•	na
Ramp Door with Beavertail	opt	opt	opt	opt	•
Idler Axles on 3,000 lb. Single Axle Models*	•	na	na	•	na
Electric Brakes on Models with 3,500 lb. Axle or Greater	•	•	•	•	•
16ò On-Center Wall Posts	•	•	•	•	•
24ò On-Center Floor and Ceiling	•	•	•	•	•
3/4ò Plywood Floor	•	•	•	•	•
32ò Side Door on Models Wider than 5ô **	•	•	•	•	•
(1) 12-Volt Dome Light with Switch on 5ô Wides	•	na	na	na	na
(2) 12-Volt Dome Lights with Switch on Models Wider than 5ô	•	•	•	•	•
.030 Smooth Aluminum Exterior	•	•	•	•	•
5ô Interior Height on 5ô Wides	•	na	na	na	na
6ô Interior Height on 6ô & 7ô Wides	•	7' only	•	•	na
6ô 9-1/2ò Interior Height on 8.5ô Wides***	•	•	•	•	•
Safety Chains	•	•	•	•	•
Screwless ñS-Lockò Front	•	•	na	na	•
4-Way Molded Plug on Idler Axle Models	•	na	na	•	na
7-Way Molded Plug on Electric Brake Models	•	•	•	•	•
2ò Coupler Std. on 3,000 and 3,500 lb Single Axle Models	•	na	na	•	na
2-5/16ò Coupler Std. on Models w\Greater than 3,500 lb. Axles	•	•	•	•	•
2ò Adjustable Pin Box on Fifth Wheel Models	na	•	na	na	na
2-5/16ò Coupler on Gooseneck Models	na	•	na	na	na

* Your state laws may require a brake axle. Please check with your dealer. When brakes are installed, they are installed on **all** axles!

** For 10ô long tandem axle models, a 24ò side door is used due to space limitations.

*** 6ô 7-1/2ò on models that use 8ò I-beam. 6ô 9-1/2ò on models that use 6ò I-beam. Useable height will be reduced by approximately 2ô from ceiling lights. Useable height at the sidewalls is apx. 5ò less. Please see your dealer for more information.

"U" TAG MODEL

Width	Axle	Length
5'	Single 3,000 lb.	8ô
		10ô
6'	Single 3,000 lb.	10ô
		12ô
		14ô
	Single 3,500 lb.	10ô
		12ô
	Tandem 3,500 lb.	10ô
		12ô
		14ô
		16ô
7'	Tandem 3,500 lb.	12ô
		14ô
		16ô
		18ô
		20ô
8.5'	Tandem 3,500 lb.	16ô
		18ô
		20ô
		22ô
		24
	Tandem 5,200 lb.	18ô
		20ô
		22ô
		24ô
		26ô
		28ô

"U" 5th WHEEL-GOOSENECK

Width	Axle	Length
8.5'	Tandem 5,200 lb.	28ô
		30ô
		32ô
		34ô
		36ô

"UW" MODEL

Width	Axle	Length
7'	Tandem 3,500 lb.	15ô
		17ô
		19ô
		21ô
		23ô
8.5'	Tandem 3,500 lb.	17ô
		19ô
		21ô
		23ô
		25
	Tandem 5,200 lb.	19ô
		21ô
		23ô
		25ô
		27ô

Note: The UW is a Wedge nose version of the U model. The Wedge nose is approximately 5ô long and is available on 6ô, 7ô, and 8.5ô wide models.

"UV" MODEL

Width	Axle	Length
6' 24" V-Nose	Single 3,000 lb.	10ô
		12ô
		14ô
	Single 3,500 lb.	10ô
		12ô
	Tandem 3,500 lb.	10ô
		12ô
		14ô

"UV" MODEL

Width	Axle	Length
7' 30" V-Nose	Tandem 3,500 lb.	12ô
		14ô
		16ô
		18ô

"USN" SLOPE NOSE

Width	Axle	Length
8.5'	Tandem 3,500 lb.	20ô
		22ô
	Tandem 5,200 lb.	20ô
		22ô
		24ô

Note: The 8.5ô speciýcations are also available on 8ô wide models. The 8ô wide models are approximately 93-1/4ô wide and the 8.5ô wide models are approximately 100ô wide.

Note: All 7ô wide trailers are standard with 8.5ô wide track axles and no interior wheel wells. Narrow track axles with interior wheel wells are available at no extra charge.

Note: Other sizes and axle conýgurations may be available upon request. Please consult with your dealer for current availability and pricing.